

The **GUIDETTI** granulating machine **GMP 750-3K** is composed by:

- Soundproof feeding hopper suitable for manual feeding or feeding through conveyor belt.
- Feeding hopper : 712 x H502 mm.
- Flaps to reduce granulator fly-back.
- Cutting chamber with « scissors cutting action » (double angle cut) – size 419x712mm. Inclined to allow a better cutting process especially for big sized parts. All components are fixed with screws and pins. Equipped with wear resistant side plates.
- Cutting chamber self-cooling system.
- V-belts driven rotor
- Open rotor (ø419 mm), equipped with three (3) slant rotor knives.
- Rotor movement sensor, in compliance with the new C.E. security norms
- Rotor RPM 450.
- Two fixed and reversible blades, equipped with wear compensating unit.
- All knives are made in H.C.H.C. steel (54-58 HRC)
- Hand operated device to open the hopper for an easy access and cleaning.
- Two front opening screen cradles, with front removable, reversible screen ø 8 mm..
- Removable drop box for collection of plastic granules
- Electrical motor 22kW (30 HP)
- Fully soundproofed system for the whole granulator
- Low voltage control panel with safety switches
- Electric system in compliance with CE norms
- Required electrical supply : 400V 3 phases 50 Hz.
- Estimated capacity, assuming a proper feeding : up to 350-490 Kg/h with grid ø8mm



GROSS WEIGHT : KG. 1750

MACHINE IN COMPLIANCE WITH  REGULATIONS